

Equinox.



Aquarius



Aries



Capricorn



Leo



Pisces



Taurus

Equinox | Mixed

Equinox is a Stainproof SDX (Solution Dyed Nylon) tufted tile. The colours are based on earthy tones, which make Equinox perfect for commercial installations.

BILL OF QUANTITIES:

- Belgotex EQUINOX 50cm x 50cm NexBac tiles are manufactured from Stainproof SDX and Stainproof Eco SDX Blend (Solution Dyed Nylon).
- This product is to be laid in accordance with the SANS 10186 fitting code of practice.
- Belgotex EQUINOX can be installed in the following directions: tessellated, random and ashlar.
- Belgotex recommends the use of carpet protector mats where castor wheels are used.

** Weighted Average *** Also available in 60 x 60cm, 1m x 50cm, 1m x 1m NexBac tiles, 25cm x 100cm and 30cm x 120cm NexBac plank tiles. EcoBac is standard for 50 x 50cm tiles in stock and available on request for 1m x 1m tiles. As these sizes and backings are not standard, minimum production quantities apply. Please contact your nearest Belgotex representative for more information.

Extended Specifications

	NexBac Tiles
Construction	Tufted Multi Scroll Loop Pile
Product Description	Heavy Commercial, SDN, Tufted Loop Pile, Bitumen Tile
Yarn Type	Stainproof SDX (Solution Dyed Nylon)
Yarn Mass	575g/m ²
Recycled Content	EcoBac/NexBac Eco (on request only) & Pile Yarn (certain colours only)
Use Classification	Heavy Commercial
Pile Height	2.5mm, 4.5mm, 5.5mm (±0.5mm)
Total Thickness	8mm (±0.5mm)
Total Mass	±4295g/m ² **
Standard Tile Size	50 x 50cm***
Machine Gauge	1/10"
Stitches/10cm	45
Fire Index	2 (SANS 10177-IV)
Colour fastness to:	
(i) Light	7 (ISO 105-B02)
(ii) Rubbing	(a) Wet 4-5 (ISO 105-X12)
Rubbing	(b) Dry 4-5 (ISO 105-X12)
(iii) Water	4-5 (ISO 105-E01)
Electrostatic Propensity	Less than 2.0kV (ISO 6356 & EN1307)
Static Control	Permanent
VOC Tested	Passed

