



Diagonals.

A diagonally textured floorcovering suited to general commercial applications. Mix one part Diagonals with one part imagination and you’ll be absolutely astonished at the patterns that you can create.

Product Information

The texture of Diagonals also has an interesting effect on shading, which enhances the pattern to add zest to any area. Diagonals is made of Stainproof

Miracle Fibre (Polypropylene) offering superior colour fastness and resistance to stains and soiling.



Bistro



Cadet Blue



Coconut



Cornsilk



Granite



Midnight



Oxford



Squirrel



Wedgewood

- BILL OF QUANTITIES:**
- Belgotex DIAGONALS 50cm x 50cm ResinBac and NexBac tiles are manufactured from Stainproof Miracle fibre (Polypropylene) & Stainproof Eco Fibre Blend (Polypropylene).
 - This product is to be laid in accordance with SANS 10186 fitting code of practice.
 - Belgotex DIAGONALS ResinBac and NexBac tiles must be tessellated at installation.
 - Belgotex recommends the use of carpet protector mats where castor wheels are used.

**** Weighted Average *** Also available in**
60 x 60cm, 1m x 50cm, 1m x 1m NexBac tiles, 25cm x 100cm and 30cm x 120cm NexBac plank tiles. As these sizes are not standard, minimum production quantities apply. Please contact your nearest Belgotex representative for more information.



Diagonals | Squirrel

Extended Specifications

Construction	ResinBac Tiles Structured Needlepunch	NexBac Tiles Structured Needlepunch
Product Description	Heavy Commercial, PP, Needlepunch, ResinBac Tile/Broadloom	Heavy Commercial, PP, Needlepunch, Bitumen Tile
Fibre Type	Stainproof Miracle Fibre (Polypropylene)	Stainproof Miracle Fibre (Polypropylene)
Fibre Mass	920g/m2	920g/m2
Recycled Content	Face Fibre (Certain colours only)	Face Fibre (Certain colours only) and Backing (NexBac Eco on request)
Use Classification	Heavy Commercial	Heavy Commercial
Total Thickness	8mm (±0.5mm)	9.5mm (±0.5mm)
Total Mass	±1370g/m2**	±3945g/m2**
Standard Tile Size	50 x 50cm	50 x 50cm***
Fire Index	2 (SANS 10177-IV)	3 (SANS 10177-IV)
Colour fastness to:		
(i) Light	7 (ISO 105-B02)	7 (ISO 105-B02)
(ii) Rubbing	(a) Wet 4-5 (ISO 105-X12)	(a) Wet 4-5 (ISO 105-X12)
Rubbing	(b) Dry 4-5 (ISO 105-X12)	(b) Dry 4-5 (ISO 105-X12)
(iii) Water	4-5 (ISO 105-E01)	4-5 (ISO 105-E01)
Electrostatic Propensity	Less than 2.0kV (ISO 6356 & EN1307)	Less than 2.0kV (ISO 6356 & EN1307)
Static Control	Permanent	Permanent
VOC Tested	Passed	Passed