



# Mod Design Collection: Crossfire.

Make a statement in hip and happening heavy commercial areas with big and bold stripes on a light or dark grey background in either light-on-dark or dark-on-light options, combine the two or add a pop of colour with one of the bright and cheerful colourways that are also available in this range.

### Product Information

Mix 'n match tiles and different lay directions for texture and tone in heavy traffic areas and even use them to direct

customers to different areas within a commercial space, office or retail environment.



Ash Grey



Dark Charcoal



Disco Green\*



Explosion\*



Fearless\*



Laser Beam\*



Rebel\*



Supersonic\*

**\*Non-stocking Colours**  
As these colours are non-stocking, minimum production quantities apply. Please contact your nearest Belgotex representative for more information.

- BILL OF QUANTITIES:**
- Belgotex CROSSFIRE 50cm x 50cm NexBac tiles are manufactured from Stainproof SDX and Stainproof Eco SDX Blend (Solution Dyed Nylon).
  - This product is to be laid in accordance with the SANS 10186 fitting code of practice.
  - Belgotex CROSSFIRE can be installed in the following directions: tessellated, monolithic, random and ashlar.
  - Belgotex recommends the use of carpet protector mats where castor wheels are used.

Mod Design Tufted Tile Collection: Crossfire | Ash Grey, Dark Charcoal & Disco Green



### Extended Specifications

Construction	Tufted Multi Scroll Loop Pile
Product Description	Heavy Commercial, SDN, Tufted Loop Pile, Bitumen Tile
Yarn Type	Stainproof SDX and Stainproof Eco SDX (Solution Dyed Nylon)
Yarn Mass	630g/m2
Recycled Content	EcoBac (EOS)/NexBac Eco (available on request only) & Pile Yarn
Use Classification	Heavy Commercial
Pile Height	2mm, 4mm, 5mm (±0.5mm)
Total Thickness	7mm (±0.5mm)
Total Mass	±4275g/m2**
Standard Tile Size	50 x 50cm***
Machine Gauge	1/10"
Stitches/10cm	45
Fire Index	2 (SANS 10177-IV)
Colour fastness to:	
(i) Light	7 (ISO 105-B02)
(ii) Rubbing	(a) Wet 4-5 (ISO 105-X12)
Rubbing	(b) Dry 4-5 (ISO 105-X12)
(iii) Water	4-5 (ISO 105-E01)
Electrostatic Propensity	Less than 2.0kV (ISO 6356 & EN1307)
Static Control	Permanent
VOC Tested	Passed



\*\* Weighted Average   \*\*\* Also available in 60 x 60cm, 1m x 50cm, 1m x 1m NexBac tiles, 25cm x 100cm and 30cm x 120cm NexBac plank tiles. EcoBac is available on request for 50 x 50cm and 1m x 1m tiles. As these sizes and backings are not standard, minimum production quantities apply. Please contact your nearest Belgotex representative for more information.