



Astral.



Astral | Breeze

The flooring complies with the EN 649 (34-43) and has group M(K4) wear rating. It is suitable for normal to heavy traffic areas. Astral is fungicidal and antibacterial. It receives a protective PUR factory seal: a good foundation for routine maintenance.



1005 Teak




1006 Almond



1007 Breeze



1010 Jade



1013 Shale



2002 Rust



2016 Smoked

Drawing Inspiration
Astral is a homogeneous calendered vinyl floor covering available in sheets, with colouration throughout the thickness of the material.



Extended Specifications

Use Classification	34-43 (EN 685)	Heavy Commercial
Total Thickness	2mm	
Weight	3300g/m2	
Width	2m	
Roll Length	20Lm	
K Rating	K4	
Wear Group	M (EN 649)	
Wear Resistance	<7.5mm3 (EN 660.2)	
Fire Rating	Bfl-s1 (EN 13501-1)	2 (SANS 10177-4)
Slip Resistance	R9 (DIN 51130/BGR 181)	
Static Electrical Propensity	< 2kV (EN 1815)	
Dimensional Stability	≤ 0.4% (EN 434)	
Residual Indentation	0.05mm (EN 433)	0.08mm (SANS 786:2007)
Thermal Conductivity	0.25 W/(m.K) (EN 12524)	
Colour fastness	≥6° (EN 20105 - B02)	
Chemical Resistance	Yes (EN 423)	
Antibacterial & Fungicidal		
Treatment	Yes	
Surface Treatment	PUR	