Storm.





Acid Rain



Avalanche



Blizzard



Gale Force



Hail Damage



Now, Belgotex introduces Storm, an elegant tufted tile range that will change your environment in a remarkable way. Our Storm carpets rejuvenate, refresh and transform any heavy commercial setting by combining stunning stylish interior design with innovation, value and easy care.

Product Information

The Storm range offers an extensive selection of colour options, with textured vertical stripes in a subtle pattern, enabling you to mix it up or create a fluid one-colour look - and to bring a contemporary style to any modern commercial interior.

The practical, durable and low maintenance product benefits make it optimal for any heavy traffic, retail or commercial applications.

This Tufted Multi Scroll Loop Pile range is also a Stainproof SDX (Solution Dyed Nylon) product, with the dimensionally stable backing system, NexBac. It conforms to the coveted Global GreenTag Scheme and qualifies for GBCSA level A, Green Star SA Interiors v1 credits.

BILL OF QUANTITIES:

- Belgotex STORM 50cm x 50cm NexBac tiles are manufactured from Stainproof SDX and Stainproof Eco SDX Blend (Solution Dyed Nylon).
- · This product is to be laid in accordance with the SANS 10186 fitting code of practice.
- Belgotex STORM can be installed in the following directions: tessellated & ashlar.
- Belgotex recommends the use of carpet protector mats where castor wheels are used.

** Weighted Average *** Also available in 60 x 60cm, 1m x 50cm, 1m x 1m NexBac tiles, 25cm x 100cm and 30cm x 120cm NexBac plank tiles. EcoBac is available on request for 50 x 50cm and 1m x 1m tiles. As these sizes and backings are not standard, minimum production quantities apply. Please contact your nearest Belgotex representative for more information.

Extended Specifications

Construction **Product Description**

Yarn Mass

Pile Height

Total Mass

Tufted Multi Scroll Loop Pile Heavy Commercial, SDN, Tufted Loop Pile, Bitumen Tile

Yarn Type Stainproof SDX and Stainproof Eco SDX

(Solution Dyed Nylon)

500a/m2

Recycled Content Backing: EcoBac (EOS)/NexBac Eco

(available on request only) & Pile Yarn (certain colours only)

Use Classification Heavy Commercial 2.5mm to 5mm (±0.5mm) Total Thickness 6mm (±0.5mm) ±4145g/m2** Standard Tile Size 50 x 50cm*** Machine Gauge 1/10"

Stitches/10cm 2 (SANS 10177-IV) Fire Index

Colour fastness to: (i) Light (ii) Rubbing Rubbing

(iii) Water **Electrostatic Propensity** Static Control

4-5 (ISO 105-E01) Less than 2.0kV (ISO 6356 & EN1307)

(a) Wet 4-5 (ISO 105-X12)

(b) Dry 4-5 (ISO 105-X12)

7 (ISO 105-B02)

VOC Tested

Permanent